

AGRI SHIFT UTTO PRO

PRODUCT DESCRIPTION

Agri Shift UTTO Pro has been engineered for various hydraulic and hydrostatic systems as well as almost all tractors' transmission systems. The product has passed the requirements for the Universal Tractor Transmission Oil (UTTO) specification, Case New Holland CNH MAT 3540 which includes frictional requirements for wet braking systems. The product offers exceptional protection of gears, transmissions, and powertrain components. Agri Shift UTTO Pro also meets a wide range of transmission specifications offering maximum protection against mechanical wear, oxidative corrosion, in a wide range of hydrostatic transmission systems. Superior additives provide excellent friction control, chatter suppression and prolonged service life of wet braking systems. Agri Shift UTTO Pro exhibits high shear stability and good low temperature performance for agricultural, construction and industrial equipment.

APPLICATIONS & BENEFITS

- Agri Shift UTTO Pro meets multiple specifications – suitable for a wide range of agricultural applications, reducing oil inventories.
- Meets Case New Holland CNH MAT 3540 plus most modern agricultural industry specifications.
- Suitable for use in wet braking systems, transmissions, and hydraulic systems.

PACK SIZES AVAILABLE

20L - 200L

SPECIFICATIONS

- | | |
|---|---|
| <ul style="list-style-type: none">• API GL-4• Allison C-4• AGCO POWERFLUID 821XL• Caterpillar TO-2• CASE MS 1210• Case New Holland CNH MAT3540• Case New Holland CNH MAT3525• Case New Holland CNH MAT3509• Case New Holland CNH MAT3505• Fendt• FNHA-2-C-200.00• FNHA-2-C-201.00• Ford ESN-M2C86-B• Ford ESN-M2C86-C• Ford ESN-M2C134-D• HCE-102• HCE-102W• John Deere JDM J20C | <ul style="list-style-type: none">• Komatsu AXO80• Kubota UDT Fluid• Massey Ferguson CMS M1145• Massey Ferguson CMS M1143• Massey Ferguson CMS M1141• Massey Ferguson CMS M1135• Valtra G2-08• Volvo WB 101• ZF TE-ML 03E• ZF TE-ML 05F• ZF TE-ML 06E• ZF TE-ML 06F• ZF TE-ML 06K• ZF TE-ML 17E• ZF TE-ML 21F |
|---|---|

TYPICAL CHARACTERISTICS

AGRI SHIFT UTTO PRO	UNITS	VALUES
VISCOSITY	cSt @ 40°C	57.51
	cSt @ 100°C	9.708
SPECIFIC GRAVITY	@ 15°C	0.875
VISCOSITY INDEX		154
POUR POINT	°C	-42
FLASH POINT	°C	210

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.