

EXPERT GT 15W-40**PRODUCT DESCRIPTION**

Vertex Expert GT 15W-40 is a premium quality multi grade engine oil formulated with select base oils and advanced additives to deliver outstanding engine performance and protection for today's Gasoline, LPG and Light Diesel engine powered cars and trucks. It meets the performance requirement of API SP and provides superior piston cleanliness, wear protection, fuel efficiency and prolonged engine life.

APPLICATIONS & BENEFITS

- Meets API SP / CF.
- Suitable for Gasoline, LPG and Light Diesel Engines.
- Multigrade properties ensure excellent engine protection over a wide temperature range.
- Group 2 Hydrocracked Base Oils offer superior engine protection, reduced wear, and improved fuel economy.
- Advanced additive package ensures engine cleanliness and sludge control.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

- API SP / CF

TYPICAL CHARACTERISTICS

EXPERT GT 15W-40	UNITS	VALUES
VISCOSITY	cSt @ 40°C	113.1
	cSt @ 100°C	14.9
SPECIFIC GRAVITY	@ 15°C	0.878
VISCOSITY INDEX		136
POUR POINT	°C	-27
FLASH POINT	°C	220

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 23 January 2026.