

TRANSMATIC CVT MV PLUS

PRODUCT DESCRIPTION

Transmatic CVT MV Plus is a Synthetic Transmission Fluid blended with high-performance synthetic base oils and high-performance additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents. Transmatic CVT MV Plus is a multi-vehicle automatic transmission fluid which provides suitable performance in a wide range of CVT-equipped passenger vehicles which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance in modern CVT transmissions.

APPLICATIONS & BENEFITS

- High performance additives and synthetic base stocks capable of servicing a wide range of CVT transmissions.
- Provides excellent friction, oxidation, and thermal stability.
- Outstanding anti-wear properties and oil film thickness.
- Excellent shear stability for consistent shift.
- Compatible with a wide range of seals.

PACK SIZES AVAILABLE

1L - 5L - 20L - 60L - 200L - 1000L IBC

SPECIFICATIONS

- | | | |
|---|--|---|
| • AUDI/ VW P/N G 052 180 (-A2) | • GM CVTF I-GREEN2 | • SHELL GREEN 1V |
| • AUDI/ VW P/N G 052 516 A2 | • GM CVT P/N 19260800 | • SUBARU LINEARTRONIC CVTF |
| • BMW/ MINI/ PUNCH EZL 799 | • GM DEX-CVT | • SUBARU LINEARTRONIC CVTF-II; P/N K0425Y0711 |
| • BMW/ MINI/ PUNCH EZL 799A | • HONDA CVTF P/N 08200-9006 | • SUBARU LINEARTRONIC CV-30 P/N K0425Y0710 |
| • BMW P/N 83 22 0 136 376 | • HONDA HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH] | • SUBARU e-CVTF |
| • BMW P/N 83 22 0 429 154 | • HONDA HCF-2 P/N 08200-HCF2 | • SUBARU i-CVTF |
| • CHRYSLER / FCA MOPAR CVTF+4 P/N 05191184A | • MAZDA CVTF 3320 | • SUBARU HIGH TORQUE P/N K0421Y0700 |
| • DAIHATSU AMMIX CVTF- DFE | • MERCEDES BENZ MB 236.20 | • SUZUKI CVT FLUID GREEN 1 |
| • DAIHATSU AMMIX CVTF- DTC | • MINI COOPER ZF CVT V1 | • SUZUKI CVT FLUID GREEN 2 |
| • DODGE/ JEEP NS-2 | • MITSUBISHI DIAMOND GREEN CVTF-J1 | • SUZUKI CVTF 3320 |
| • FCA CVTF+4 P/N 05191184AA | • MITSUBISHI DIAMOND GREEN CVTF-J4 | • SUZUKI NS-2 |
| • FORD CFT23 | • NISSAN NS-1 | • TOYOTA / LEXUS FE |
| • FORD CFT30 | • NISSAN NS-2 | • TOYOTA / LEXUS TC |
| • FORD MERC C | • NISSAN NS-3 | |
| • FORD WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT | • RENAULT ELFMATIC | |
| | • SATURN P/N 22688912 | |

TYPICAL CHARACTERISTICS

TRANSMATIC CVT MV PLUS	UNITS	VALUES
VISCOSITY	cSt @ 40°C	34.4
	cSt @ 100°C	7.2
SPECIFIC GRAVITY	@ 15°C	0.8540
VISCOSITY INDEX		180
POUR POINT	°C	-45

FLASH POINT	°C	198
BROOKFIELD VISCOSITY	@ -40°C	13500
APPEARANCE	VISUAL	Green

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 12 February 2026.