

TRANSMATIC 3 SYN

PRODUCT DESCRIPTION

Transmatic 3 SYN is formulated with synthetic base stock to address the need for a universal transmission fluid servicing a wide range of vehicles. Extensive research and advanced additives systems ensure that Transmatic 3 SYN can service the highest possible range of modern automatic transmissions (excluding CVT & DCT transmissions). The product is backward compatible with older transmissions such as those requiring Dexron II and III. Transmatic 3 SYN is primarily designed for passenger car vehicles but due to a robust synthetic formulation can be used in some commercial vehicles requiring Allison C-4. Transmatic 3 SYN provides absolute best in class for smooth shifting, component protection, extended drain intervals and enhanced fuel consumption.

APPLICATIONS & BENEFITS

- Suitable for a wide range of vehicles reducing the need to carry multiple transmission fluids.
- Synthetic formulation provides best in class thermal stability and oxidation resistance.
- Outstanding anti-wear additives extend the life of all transmission components.
- Viscosity stability over a wide range of temperatures ensures smooth gear shifting.
- Special additives provide seal protection and longevity.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

- Allison C-4
- Dexron II D/E
- Dexron III H
- GM Type A & TASA
- Ford Mercon
- Ford ESP-M2C166-H
- Ford ESP-M2C138-CJ
- Mercedes Benz 236.2

TYPICAL CHARACTERISTICS

TRANSMATIC 3 SYN	UNITS	VALUES
VISCOSITY	cSt @ 40°C	35.7
	cSt @ 100°C	7.3
SPECIFIC GRAVITY	@ 15°C	0.853
VISCOSITY INDEX		175
POUR POINT	°C	-45
FLASH POINT	°C	194

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 20 December 2024.